Specifications

Material

» Laminated impact acrylic

Finish

» Gloss

Sheet Size

» 24" x 48¾" (610 x 1238mm)

Thickness 2-ply

- » 1/16" (1.6mm) Use 422 as first digits in item code.
- » 1/8" (3.2mm) Use 442 as first digits in item code. (Gauges are approximate.)

Thickness 3-ply

- » 1/16" (1.6mm) Use 423 as first digits in item code.
- » 1/8" (3.2mm) Use 443 as first digits in item code.

Usage

- » Interior signage
- » Exterior signage
- » Personal identification

Engraving Method

» Rotating carbide

Cutting Depth

» .012" (.30mm)

Fabrication

- » Saws
- » Drills
- » Bevels
- » Heat bendable
- » Screen prints
- » Hot stamps
- » Bonds
- » UV stable
- » Outdoor Weatherable

Visit www.rowmark.com for Rowmark's complete line of products for rotary engraving, laser engraving and sublimation.

Find answers to all your auestions in the Technical Help section. Be sure to check out support tools under the Sales Tools and Downloads sections.

To request a sample or promotional literature, please call 1-877-ROWMARK (419-429-3160) or email samples@rowmark.com. For technical assistance, call 1-877-ROWMARK (419-429-3160), visit www.rowmark.com or email inquiries@rowmark.com.

Can't find exactly what you're looking for? We can build any combination of cap and core within the Lacquers product line. Contact your authorized Rowmark distributor or speak with one of our customer service specialists at 1-800-243-3339 (419-425-2407).







Lacquers Sign Kit item #9025

You may place your Lacquers Sign Kit order at www.rowmark.com, or fabricate the signs on your own using the file found under the downloads section of our website.















rowmark.com / 1.877 ROWMARK / samples@rowmark.com



