

### Description

Translucent, white, matte special cast PVC film with 30% light transmission, providing improved light distribution and uniformity in illuminated signs. The reduced surface gloss inhibits undesired reflection.

### Release Paper

Silicone coated paper on one side, 137 g/m<sup>2</sup>

### Adhesive

Solvent polyacrylate, permanent

### Area of use

This film is specially designed for high quality applications, such as onto light boxes and for the production of internally illuminated signs. It can also be used on backlit acrylic glass, glass and pre-tensioned banner material. Suitable for use on cutting plotters and for thermoforming.

### Technical Data

<b>Thickness*</b> (without paper and adhesive)	55 micron
<b>Dimensional stability</b> (FINAT TM 14)	Adhered to steel, no shrinkage in cross direction, shrinkage in length 0,1 mm max.
<b>Temperature resistance***</b>	Adhered to acrylic glass, -40° C to +80° C, no variation
<b>Resistance to cleaning agents</b>	Adhered to acrylic glass, 8h in mild detergents (0,5% household cleaning agents) at room temperature and 65° C, no variation
<b>Adhesive power*</b> (FINAT TM 1, after 24h)	18 N/25 mm glass 16 N/25 mm acrylic glass
<b>Tensile strength</b> (DIN EN ISO 527)	Along: min. 21 MPa Across: min. 21 MPa
<b>Elongation at break</b> (DIN EN ISO 527)	Along: min. 120% Across: min. 120%
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> 8° C
<b>Service life by specialist application</b>	10 years

Under vertical outdoor exposure (normal climate of Central Europe). The durability of the film to a large extent is dependent on the climate zone and angle of exposure. Further information about the service life can be found on our website at [www.orafol.com/gp/europe/en/support](http://www.orafol.com/gp/europe/en/support).

\* average \*\* in original packaging, at 20° C and 50% relative humidity \*\*\* normal climate of Central Europe

### Note

Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material.

Furthermore, the application information published by ORAFOL must be considered.

The batch traceability according to ISO 9001 is possible on the basis of the roll number.

### **IMPORTANT NOTICE**

All ORACAL® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORACAL® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORACAL® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.