HP Latex 700 W Printer

Win high-value jobs, equipped with white ink, and sharpen your sustainability edge with HP Latex





Access white and produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colours at high speed, get striking contrast using pure blacks, and expect sharp 4point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

Beat your deadlines with smart, efficient printing

- Fast saturated colour up to 31 m²/hr outdoor, 21 m²/hr indoor.2
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 55 kg.

Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks-no HAPs³, no required hazard warning labels, and odorless prints.4
- Zero landfill—local outer carton recycling, free take-back of inner ink bag/printhead, HP Planet Partners.⁵
- Choose from a wide range of compatible ecoconscious media.⁶
- HP Latex prints are recyclable, returnable, or non-hazardous and safe for disposal.⁷

For more information, please visit http://www.hp.com/go/latex700series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (L*:4.16 – a:0,48-b:2,34) with 160% UF printmode using HP 832 1-liter White Latex Ink Cartridge. Visual opacity = 91%. ² Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image

³ HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.

⁴ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. ⁵ The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For ink bag and printhead take back, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal. See http://www.hp.com/go/mediasolutionslocator

⁷ Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details. HP large format printing materials, both unprinted and printed with Original HP Latex Inks, are non-hazardous and safe for disposal. Contact your local waste management authority for local area-specific instructions

Technical specifications

| Print | |
|--|--|
| Printing modes | 105 m²/hr - Max Speed (1-pass) 21 m²/hr - High Speed (4-pass) 21 m²/hr - Production Fast (6-pass) 17 m²/hr - Production Quality, Textiles and Backlits (8-pass) 16 m²/hr - High Saturation (12-pass) 12 m²/hr - High Saturation Backlits and Textiles (14-pass) 17 m²/hr - White Spot (60%) 9 m²/hr - White Duterflood (60%) 3 m²/hr - White Underflood (100%) 2 m²/hr - Jayers Day & White (160%) ¹ |
| Print resolution | Up to 1200 x 1200 dpi |
| ink types | Water-based HP Latex Inks |
| ink cartridges | 9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Overcoat) |
| Cartridge size | 1L |
| Printheads | 10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Overcoat) |
| ong-term print-to-print peatability | 95% of colours ≤ 1.5 dE2000 ² |
| Media | |
| Handling | Roll feed, take-up reel, wiper roller ³ , automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper-based media, and film) |
| Media types | Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles ⁵ |
| Roll size | 254 to 1625-mm rolls (580 to 1625-mm rolls with full support) |
| Roll weight | 55 kg |
| Roll diameter | 250 mm |
| Thickness | Up to 0.5 mm |
| Applications | Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers |
| Connectivity | |
| nterfaces | Gigabit Ethernet (1000Base-T) |
| Dimensions (w x d | xh) |
| Printer | 2583 x 852 x 1402 mm |
| Shipping | 2800 x 1130 x 1270 mm |
| Operating area | 2793 x 2100 mm |
| Weight | |
| Printer | 267 kg |
| Shipping | 368 kg |
| What's in the box | HP Latex 700 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords, air purgers, Z-in spindle adaptor |
| Environmental ran | iges |
| | |
| Operating temperature | 15 to 30°C |
| | 15 to 30°C 20 to 80% RH (non-condensing) |
| Operating humidity | |
| Dperating humidity Acoustics | |
| Operating humidity Acoustics Sound pressure | 20 to 80% RH (non-condensing) |
| Operating humidity Acoustics Sound pressure Sound power | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) |
| Operating humidity Acoustics Sound pressure Sound power Power | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) |
| Derating humidity Acoustics Sound pressure Sound power Power Consumption | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.5-2.6 kW (5 kW peak) (printing), 95 W (ready) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.5-2.6 kW (5 kW peak) (printing), 95 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max |
| Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.5-2.6 kW (5 kW peak) (printing), 95 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max |
| Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.5-2.6 kW (5 kW peak) (printing), 95 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and |
| Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety | 20 to 80% RH (non-condensing) 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.5-2.6 kW (5 kW peak) (printing), 95 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCD) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICSS), EU (EMC Directive), Australia and |

Ordering information

Product

Y01123A HP Latex 700 W Printer

| Accessories | | |
|-------------|--|--|
| 21V10A | HP Latex 700/800 User Maintenance Kit | |
| 7HR16A | HP Latex 700/800 Textile Kit Accessory | |
| 7HR18A | HP Latex 700/800 Ink Collector Foams Kit | |
| 7HR19A | HP Latex 700/800 Media Loading Accessory | |
| T7U73A | HP Latex 500/700/800 Wiper Roller | |

| HP Latex 700/800 Media Loading Accessory |
|--|
| HP Latex 500/700/800 Winer Roller |

Original HP printing supplies

| - | | |
|--------|--|--|
| 4UU93A | HP 836 White Latex Printhead | |
| 4UU94A | HP 836 Optimizer Latex Printhead | |
| 4UU96A | HP 836 Latex Maintenance Cartridge | |
| 4UV29A | HP 832 1-liter White Latex Ink Cartridge | |
| 4UV75A | HP 832 1-liter Black Latex Ink Cartridge | |
| 4UV76A | HP 832 1-liter Cyan Latex Ink Cartridge | |
| 4UV77A | HP 832 1-liter Magenta Latex Ink Cartridge | |
| 4UV78A | HP 832 1-liter Yellow Latex Ink Cartridge | |
| 4UV79A | HP 832 1-liter Light Cyan Latex Ink Cartridge | |
| 4UV80A | HP 832 1-liter Light Magenta Latex Ink Cartridge | |
| 4UV81A | HP 832 1-liter Optimizer Latex Ink Cartridge | |
| 4UV82A | HP 832 1-liter Overcoat Latex Ink Cartridge | |
| 4UV83A | HP 832 Ink Mix Container | |
| 4UV95A | HP 836 Black/Cyan Latex Printhead | |
| 4UV96A | HP 836 Magenta/Yellow Latex Printhead | |
| 4UV97A | HP 836 Light Cyan/Light Magenta Latex Printhead | |
| 4UV98A | HP 836 Overcoat Latex Printhead | |
| | | |

Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁶, FSC[®] certified⁷, meets AgBB criteria⁸) HP Photo-realistic Poster Paper

HP Premium Satin Carvas HP Premium Satin Carvas HP Prime Matte Air GP (REACH compliant⁹) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant⁹)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U13DCE HP 2 year Next Business Day with Defective Media Retention U13DHE HP 3 year Next Business Day with Defective Media Retention U13DMPE HP 1 year Post Warranty Next Business Day with Defective Media Retention U13DSPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard¹ Can win new business with odorless prints, UL ECOLOGO®/UL GREENGUARD Gold Certified ink, and more² Eco-Carton replaces plastic cartidge with 80% reduction in plastic, activese 56% CO2 reduction³ Zero landfill—local outer carton recycling, free take-back inner ink bag via HP Planet Partners⁴

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

¹ See http://www.roadmaptozero.com. Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin. ² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. For certifications, see http://www.ulcom/Ea. and http://www.ulcom/Eg. ³ C02e reduction based on moving from plastic ink cartridge to cardboard HP Eco-Carton ink cartridge, with annual schuring savings of 291 tons and transport savings of 8 fors. Equivalent to 1,194,028 km (741,935 miles) driven by an average passenger vehicle or over 38 million smartphones charged. ⁴ The ink cartridge HP Eco-Carton outer cartor ins 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For take-back of ink bag/printhead/prints, visit http://www.hp.com/Ecycle to see how to participate and for HP Planet Partners program availability, program may not be available in your jurisdiction.

¹ Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects. ² The colour variation between printed jobs has been measured at 12 pass mode on vinv1 media following best practices for tiling layouts and within this limit "95th percentile of pairwise colour differences (95% of colours) = 1 dE2000. Reflective measurements on a 943 colour target under CIE standard Illuminant D50, and according to the standard CIE 2000. Backlit substrates measured in transmission mode may yield different results.

dE2000. Backlit substrates measured in transmission mode may yield different results. ³ Wiper roller is an optional accessory. ⁴ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test. ⁵ Textle Rir Accessory required for long runs of textile and porous textile. ⁶ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor ari during product usage. For more information, visit http://www.ulcom/go or http://www.greenguard.org. ⁷ Trademark license code FSC-C115319. ⁸ With HP Latex links, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://unweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building. ⁹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



